

HF/NFC or LF TEAR RFID KEY FOB

@RFID offers a wide range of RFID transponders.

The **TEAR RFID KEY FOB** integrate an NFC/HF or LF INLAY to provide best possible read range.

The assembly of the ABS housing is done by automatic ultrasonic welding machinery to achieve IP67 IP protection to resist water immersion and mechanical stress.

OPTIONS:

- Logo ink jet or tampon print
- Serial- or UID number Laser engraving
- Chip encoding is available.
- Customized colour on request

Applications for HF/NFC or LF KEY FOB:

- Access Control
- Pay Back System
- Loyalty System
- Membership System
- Time Attendance
- Your idea/application



Frequencies/Chips:

HF/NFC: ISO 14443A NXP M ifare-/NTAG-/@RFID-compatible Series : 13,56MHz

ISO 15693 NXP I-Code Series

LF: EM4200, HITAG S, ATA5577, @RFID-compatible Series : 125 kHz

Technical:

Material:	ABS ultrasonic welded housing
Dimension:	40 x 31 x 4,8 mm, 4mm hole
Weight:	5 g
Colours:	Black, Blue, Green, Grey, Red, Yellow, Your Colour
Operating Temperature:	-25° ... +75°C
Read Range:	NFC/ISO14443 ≤ 50 mm
(Depends on reader etc.)	NFC/ISO15693 / LF ≤ 60 mm
Frequencies:	HF 14 MHz ±500 kHz
	LF 125 kHz ± 6 kHz
Antenna:	Copper Coil wound
Environmental:	RoHS compliant
Customized:	Logo / Serial No. Print, Pre-Encoded

@RFID Deutschland

udoege@arfid.eu
Tel: +49 (0)6074 86 1930
Fax: +49 (0)3212 8619290
www.arfid.eu



arfidex GmbH www.arfidex.de
Adlerstraße 2
63322 Rödermark
VAT: DE 311 20 55 73

@RFID Headquarters

sofia@arfid.eu
Tel.: +359 2 888 87 32 54
Fax: + 359 2 884 55 82
VAT: BG 175 33 66 55

arfid Ltd
Mladost 1, No.20/26
1750 Sofia, Bulgaria
www.arfid.eu